



SAFETY DATA SHEET

Revision Date 09-Mar-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name VERSACHEM MEGA BLUE RTV SILICONE GASKET MAKER 3 OZ.

Other means of identification

Product Code 77739

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex
(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|-----------------------------------|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 2 |

Label elements

Emergency Overview

Warning

Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer



Appearance Blue

Physical state Paste

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Call a POISON CENTER or doctor/physician if you feel unwell
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

26.18% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---|------------|----------|--------------|
| POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED | 70131-67-8 | 15 - 40 | * |
| CALCIUM CARBONATE | 471-34-1 | 10 - 30 | * |
| LIMESTONE | 1317-65-3 | 10 - 30 | * |
| SYNTHETIC ISOPARAFFINIC HYDROCARON | 64742-47-8 | 3 - 7 | * |
| VINYL OXIMINOSILANE | 2224-33-1 | 3 - 7 | * |
| POLYDIMETHYLSILOXANE | 63148-62-9 | 1 - 5 | * |
| STEARIC ACID | 57-11-4 | 1 - 5 | * |
| 2-BUTANONE OXIME | 96-29-7 | 1 - 5 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | Get medical advice/attention if you feel unwell. |
| Eye contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin contact | IF ON SKIN: Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Inhalation | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician. |
| Ingestion | IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician. |
| Self-protection of the first aider | Use personal protective equipment as required. |

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Flood with water to complete polymerization and scrape off floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if walked on.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.

Incompatible materials Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------------------|-----------|--|--|
| CALCIUM CARBONATE 471-34-1 | - | - | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| LIMESTONE 1317-65-3 | - | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste
Appearance Blue
Odor Mild
Odor threshold No information available

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--------------------------------|--------------------------|-------------------------|
| pH | No information available | |
| Melting point / freezing point | No information available | |
| Boiling point / boiling range | Not Applicable | Polymerization |
| Flash point | > 93 °C / > 200 °F | Tag Closed Cup |
| Evaporation rate | No information available | |
| Flammability (solid, gas) | No information available | |
| Flammability Limit in Air | | |
| Upper flammability limit: | No information available | |
| Lower flammability limit: | No information available | |
| Vapor pressure | <5 mm Hg @ 80°F | |
| Vapor density | 3.0 | Air = 1 |
| Relative density | 1.44 | |
| Water solubility | Not applicable | Polymerization |
| Solubility in other solvents | No information available | |
| Partition coefficient | No information available | |
| Autoignition temperature | No information available | |
| Decomposition temperature | No information available | |
| Kinematic viscosity | No information available | |
| Dynamic viscosity | No information available | |
| Explosive properties | No information available | |
| Oxidizing properties | No information available | |

Other Information

Softening point No information available
Molecular weight No information available
VOC Content (%) 3.1%
Density No information available
Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity
 No data available

Chemical stability
 Stable under recommended storage conditions.

Possibility of Hazardous Reactions
 None under normal processing.

Conditions to avoid
 Excessive heat. Exposure to air or moisture over prolonged periods. Heat, flames and sparks.

Incompatible materials
 Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products
 Carbon dioxide (CO₂)
 Nitrogen oxides (NO_x)
 Formaldehyde
 May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.
Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion Ingestion may cause irritation to mucous membranes.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|----------------------|-------------------------|--------------------------------------|
| POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8 | - | > 16 mL/kg (Rabbit) | > 8750 mg/m ³ (Rat) 7 h |
| CALCIUM CARBONATE 471-34-1 | = 6450 mg/kg (Rat) | - | - |
| SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8 | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat) 4 h |
| POLYDIMETHYLSILOXANE 63148-62-9 | > 17 g/kg (Rat) | > 2 g/kg (Rabbit) | - |
| STEARIC ACID 57-11-4 | - | > 5 g/kg (Rabbit) | - |
| 2-BUTANONE OXIME 96-29-7 | = 930 mg/kg (Rat) | = 0.2 mg/kg (Rabbit) | = 20 mg/L (Rat) 4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.
Target Organ Effects Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 10659 mg/kg
 ATEmix (dermal) 8982 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

94.07% of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|---|--|--|--|
| SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8 | - | 45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static | 4720: 96 h Den-dronereides heteropoda mg/L LC50 |
| 2-BUTANONE OXIME 96-29-7 | 83: 72 h Desmodemus subspicatus mg/L EC50 | 777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 760: 96 h Poecilia reticulata mg/L LC50 static | 750: 48 h Daphnia magna mg/L EC50 |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

| Chemical Name | Partition coefficient |
|-----------------------------|-----------------------|
| 2-BUTANONE OXIME 96-29-7 | 0.65 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

| | |
|-------------------------------|---|
| Disposal of wastes | Disposal should be in accordance with applicable regional, national and local laws and regulations. |
| Contaminated packaging | Do not reuse container. |
| US EPA Waste Number | Not applicable |

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

IMDG

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

| | |
|----------------------|------------|
| TSCA | Complies |
| DSL/NDSL | Complies |
| EINECS/ELINCS | Not Listed |
| ENCS | Not Listed |
| IECSC | Complies |
| KECL | Complies |
| PICCS | Complies |
| AICS | Complies |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | No |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 |
|-----------------------------|-----------------------------|
| SILICA, QUARTZ - 14808-60-7 | Carcinogen |
| ETHANOL - 64-17-5 | Carcinogen Developmental |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| LIMESTONE 1317-65-3 | X | X | X |
| ALUMINIUM POWDER 7429-90-5 | X | X | X |
| CI PIGMENT BLUE 15, CI #74160 147-14-8 | X | - | X |
| SILICA, QUARTZ 14808-60-7 | X | X | X |
| ETHANOL 64-17-5 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

| | | | | |
|--------------------|------------------|----------------|--------------------|-----------------------|
| <u>NFPA</u> | Health hazards 2 | Flammability 1 | Instability 0 | - |
| <u>HMIS</u> | Health hazards 2 | Flammability 1 | Physical hazards 0 | Personal protection B |

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 09-Mar-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet