

ITW Permatex
Versachem Brand
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924 (ChemTel)
International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: **VERSACHEM FIBERGLASS REPAIR KIT (HARDENER)**
Product Type: **Epoxy hardener**

This product appears in the following stock number(s):
90230

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
MERCAPTAN AMINE BLEND TSRN 679485-6533P	>85	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: Causes severe eye irritation. May cause severe eye irritation. May cause nose, throat and respiratory irritation. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May cause skin sensitization.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: May be injurious to eyes, skin, mucous membranes and lungs. May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Repeated skin contact may cause allergic skin reactions.

Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, get medical attention.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F (>93°C)

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact. Use water spray to cool exposed containers.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Amines, Ammonia

Unusual Fire/Explosion Hazards: Personnel in vicinity and downwind should be evacuated.

Lower Explosive Limit: n/d

Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers.

7. HANDLING AND STORAGE

Storage: Store in a cool, dry area. Store away from heat.

Handling: Avoid contact with vapors from heated material. Avoid contact with skin and eyes. Wash hands before eating and smoking. Discard contaminated leather gloves and shoes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses
Skin:	Neoprene or nitrile gloves recommended. Wash contaminated clothing before re-use.
Ventilation:	Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
Respiratory Protection:	An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colorless to light yellow liquid
Odor:	Mercaptan
Boiling Point:	Not determined
Solubility in Water:	Negligible
pH:	9.5 (5% solution or slurry in water)
Specific Gravity:	1.13
VOC(Wt.%):	0
Vapor Pressure:	Not Determined
Vapor Density (Air=1):	>1
Evaporation Rate:	Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	Will not occur
Incompatibilities:	Strong oxidizers, Amines, Peroxides, Sodium/calcium hypochlorite
Conditions to Avoid:	Heat
Hazardous Products of Combustion:	Oxides of carbon, Oxides of nitrogen, Amines, Ammonia

11. TOXICOLOGICAL INFORMATION

Eye irritation: Severe - Draize = 4.8

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:	Disposal should be made in accordance with federal, state and local regulations
US EPA Waste Number:	NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name:	Not regulated
Hazard Class:	None
UN/ID Number:	None

IATA (Air)

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/ID Number:	None

IMDG (Vessel)

Proper Shipping Name:	Not regulated
Hazard Class:	None
UN Number:	None
Marine Pollutant:	None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

15. REGULATORY INFORMATION

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 3, FLAMMABILITY 1, REACTIVITY 0

Estimated HMIS Classification: HEALTH 3, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: October 03, 2012

Revision Number: 1

ITW Permatex
Versachem Brand
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924 (ChemTel)
International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: **VERSACHEM FIBERGLASS REPAIR KIT (RESIN)**
Product Type: **Epoxy resin**

This product appears in the following stock number(s):
90230

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	>90	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: Causes moderate eye irritation. Causes moderate skin irritation. May cause skin sensitization.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Repeated skin contact may cause allergic skin reactions. Contact with product at elevated temperatures can result in thermal burns. Ingestion may cause nausea and vomiting. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed.
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >400°F (>204°C)
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Material will not burn unless preheated. Firefighters should wear self-contained breathing apparatus. Use water spray to cool exposed containers.
Hazardous Products of Combustion: Oxides of carbon, Aldehydes, Acid vapors
Unusual Fire/Explosion Hazards: May decompose above 300 degrees F.; may polymerize above 500 degrees F. in which case closed containers may rupture or explode. Fumes and vapor from thermal and chemical decomposition vary in composition and toxicity. Do not breathe fumes.

Lower Explosive Limit: n/d
Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers.

7. HANDLING AND STORAGE

Storage: Store in a cool, dry area. Store away from heat.
Handling: Avoid contact with vapors from heated material. Avoid contact with skin and eyes. Wash hands before eating and smoking. Discard contaminated leather gloves and shoes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses
Skin:	Neoprene or nitrile gloves recommended.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear viscous liquid
Odor:	Slight
Boiling Point:	Not determined
Solubility in Water:	Negligible
pH:	Neutral
Specific Gravity:	1.17
VOC(Wt.%):	0
Vapor Pressure:	Not Determined
Vapor Density (Air=1):	>1
Evaporation Rate:	<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	Will not occur
Incompatibilities:	Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines)
Conditions to Avoid:	Heat
Hazardous Products of Combustion:	Oxides of carbon, Aldehydes, Acid vapors

11. TOXICOLOGICAL INFORMATION

Oral LD50 (rat) = 11.4 g/kg
Dermal LD50 (rabbit) = >20 ml/kg
Inhalation LC50 (rat) = no deaths (4h)
IARC Group 3; Not classifiable as a carcinogen

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:	Disposal should be made in accordance with federal, state and local regulations
US EPA Waste Number:	NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name:	Not regulated
Hazard Class:	None
UN/ID Number:	None

IATA (Air)

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/ID Number:	None

IMDG (Vessel)

Proper Shipping Name:	Not regulated
Hazard Class:	None
UN Number:	None
Marine Pollutant:	None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

15. REGULATORY INFORMATION

None

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106

Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: August 16, 2012

Revision Number: 1