



2107 West Blue Heron Blvd.  
Riviera Beach, FL 33404  
Phone: 561-845-2425  
Toll Free: 800-327-6880  
www.itwconsumer.com

# Clear RTV Silicone

## Technical Data Sheet

Rev 08/07

**PRODUCT DESCRIPTION:** A silicone adhesive/sealant compound for sealing, caulking, bonding and making gaskets. Clear Silicone is a general purpose, single component, room temperature vulcanizing (RTV) compound designed for sealing of mechanical assemblies. Once cured this non-sagging silicone rubber forms a tough, flexible, waterproof seal that resists aging and weathering without hardening, shrinking or cracking. Clear Silicone cures on exposure to moisture in the air. OEM (Original Equipment Manufacture) approved.

**WORKS BEST ON:** Metal, glass, wood, plastic, silicone resin, vulcanized silicone rubber, ceramics, natural and synthetic fiber, painted surfaces, concrete and rubber. Good for weather-proofing electrical components and sealing glass. Clear silicone makes form-in-place gaskets; use to replace cork, paper, felt and rubber gaskets. Bonds, seals, repairs, mends and secures lens housing, windshields, windows, door frames, vinyl tops, pvc piping, fiberglass, tiles/fixtures. Does not bond to polyethylene or polypropylene plastics. Is not mildew resistant. Do not use on any surfaces that will be painted (complete all painting before applying silicone).

### PRODUCT FEATURES:

Tensile Strength: 310 psi

Color: Clear

Non-Flammable

Working Time: 10-15 minutes

Can be Handled In: 30 minutes

Full Bond: 12 - 24 hours (Cure times vary with temperature, humidity and gap)

Temperature Range: Flexible from -76°F to +350°F and up to 450 °F intermittent

Chemical Solvent Resistance: Automotive fluids such as motor oil, gasoline, brake fluids, transmission fluids, grease, alcohol and antifreeze mixtures

Storage: Store room temperature in unopened container.

**SURFACE PREPARATION:** Thoroughly clean all surfaces of grease, oil, traces of paint, dust, etc. with a cleaning solvent and allow to dry.

**REMOVAL METHODS:** (test inconspicuous area of item to be sure chemicals do not harm surface)

Before Cure: Wipe up excess. Solvents that can be used are isopropyl alcohol or acetone.

After Cure:

Metal/Ceramic/Glass: use a safety razor and cut at the bond line.

Fabric: Light surface adhesion on fabric may be removed by peeling. Where imbedded in fabric, may not be able to remove.

Wood: Peel off.

**HELPFUL HINTS:** Removable tape is good for putting on an area that you don't want any silicone to get on. Before the silicone cures, remove the tape.

**See MSDS for more complete information, safe handling instructions and first aid.**

Non-Regulated

Part Numbers: 12045, 25045, 73009



The technical data contained herein are intended as a reference only