



2107 West Blue Heron Blvd.
Riviera Beach, FL 33404
Phone: 561-845-2425
Toll Free: 800-327-6880
www.itwconsumer.com

Lock Lubricator, aerosol

Technical Data Sheet

Rev 12/08

PRODUCT DESCRIPTION: A pressurized lubricator that can be used on all types of lock mechanisms . . . for the car, home, office, boat, shop, etc. An occasional injection of the special lubricant will always ensure easily operating locks. Prevents seized and frozen locks . . . no more rusted locks and broken keys . . . de-icing fluid added for all-weather use.

WORKS BEST ON: Insert tip of red nozzle into key hole and press against lock. Use frequently to keep locks in prime mechanical condition. Although not harmful to original paint work, any excess spillage should be wiped off promptly. Can be used on door locks, trunk and all outdoor locks . . . prevents freezing and rusting. Works on: luggage locks, padlocks, ski rack lock, car door lock, gas tank lock, house door locks.

PRODUCT FEATURES:

Color: Clear

Waterproof

Highly Flammable (Product is an aerosol, contents under pressure)

CAUTION: Contains isopropyl alcohol. Do not use near heat, sparks or open flame. Do not puncture or incinerate container.

Temperature Range: Do not expose to temperatures above 120°F. Will not freeze to -125°F

Storage: Store in a cool, dry environment in unopened container.

REMOVAL METHODS:

Immediately wipe any excess with a damp cloth.

HELPFUL HINTS: This product is packaged in a pressurized can. Once the pressure is all used up, only the product remains. Temperature, age of product and position of the nozzle are the three major factors that can affect the performance of this product. Holding the can's valve at a slight downward angle will allow more of the product to be released each use (and less of the air pressure).

See MSDS for more complete information, safe handling instructions and first aid.

Consumer Commodity ORM-D

Part Numbers: 00205



The technical data contained herein are intended as a reference only