



2107 West Blue Heron Blvd.
Riviera Beach, FL 33404
Phone: 561-845-2425
Toll Free: 800-327-6880
www.itwconsumer.com

Sure Connect Bulb Grease

Technical Data Sheet

Rev 08/07

PRODUCT DESCRIPTION: Sure Connect Bulb Grease is a silicone dielectric grease improves connections, prevents rust and corrosion. Increases performance and extends service life of bulbs and lamps by preventing voltage leakage and protecting electrical connections from moisture, dirt and corrosion. Great lubricating properties ease the disassembly process. Protects rubber, plastic, ceramic and metal surfaces. Waterproof and corrosion resistant.

WORKS BEST ON: Light bulbs, flood lamps, decorative lighting, electrical connections, taillights, headlights, RV & ATV connections, marine connections, batteries, glove compartment, inside door trim, interior courtesy lamps, parking and turn signals, brake lights, trunk and hood lamps; also for fuses, battery terminals, ignition components and other electrical connections.

Sure Connect Bulb Grease can be used indoors and outdoors; for household, automotive, marine and shop uses. Easy in and easy out replacement for hard to reach bulbs in recess lighting so common in today's homes. Also helps prevent corrosion on electrical connections. This product prevents bulbs from sticking and breaking and ensures a positive connection and easy removal from the socket.

PRODUCT FEATURES:

Color: Translucent Paste

Waterproof

Non-Flammable

Temperature Range: Up to 540°F

Chemical Solvent Resistance: Alcohols, ketones, ethers or water

DO NOT use Dielectric Connector Grease with liquid oxygen, chlorine or peroxides. **DO NOT** use on surfaces to be painted. Not recommended for use as a lubricant for metal to metal surfaces.

Storage: Store in a cool, dry environment in unopened container.

SURFACE PREPARATION: Thoroughly clean all surfaces of grease, oil, traces of paint, dust, etc.

REMOVAL METHODS:

Spilled bulb grease will cause slippery conditions. Wipe up and clean spills immediately to prevent possibly injury.

Bulb grease can be removed with mineral spirits.

HELPFUL HINTS: Turn off electrical system. NEVER APPLY BULB GREASE TO THE INSIDE OF AN ELECTRIC LIGHT SOCKET!

See MSDS for more complete information, safe handling instructions and first aid.

Non-Regulated

Part Number: 15319, 15320



The technical data contained herein are intended as a reference only