



2107 West Blue Heron Blvd.
Riviera Beach, FL 33404
Phone: 561-845-2425
Toll Free: 800-327-6880
www.itwconsumer.com

Sure Tack Gasket Sealant

Technical Data Sheet

Rev 03/08

PRODUCT DESCRIPTION: Sure Tack Gasket Sealant holds gaskets in place to ensure proper alignment during assembly. Formulated as a sealant, it dries quickly to a high tacky film. It can be applied in advance for convenience in assembly.

WORKS BEST ON: Use on cork, rubber, paper, felt and metal gaskets.

PRODUCT FEATURES:

Senor Safe
Color: Red
Highly Flammable (Product is an aerosol, contents under pressure)
Set Time: 5 Minutes
Temperature Range: -65°F to 450°F
Chemical Solvent Resistance: automotive fluids and oils

NOT RECOMMENDED for use on parts in constant contact with gasoline.

Storage: Store in a cool, dry environment. Do not store above 120°F.
Turn can upside-down and spray to clear nozzle.

SURFACE PREPARATION: PROVIDE ADEQUATE VENTILATION. Protect work area from accidental spills. Clean surfaces to remove grease, oil, dirt or other contaminants.

REMOVAL METHODS: (test inconspicuous area of item to be sure chemicals do not harm surface)

Before cure: Wipe off with soap and water or alcohol.

After cure: After it has set use VersaChem's Gasket Remover.

HELPFUL HINTS: Clean and dry surfaces thoroughly. For proper spraying, can should be near room temperature (about 72°F). Prior to use, shake can vigorously for one minute.

Wait for solvent to evaporate before assembly. The product can be applied in advance and still remain tacky when assembled. For best coverage 2-3 light coats are recommended.

Apply removable tape to areas that should not be coated. Remove tape after your assembly.

This product is not recommended for use in pure oxygen or oxygen rich systems and should not be used as a sealant for chlorine or other strong oxidizing materials.

See MSDS for more complete information, safe handling instructions and first aid.

Consumer Commodity ORM-D

Part Number: 22108



The technical data contained herein are intended as a reference only